


HCWG

Pulse magnetic field immunity test system



HCWG pulsed magnetic field test system



overview

The HCWG series has excellent and reliable performance, beautiful appearance, fully meets IEC and GB standards, meets pulsed magnetic field (1.2/50 μ s_8/20 μ s), and reaches the international first-class level. Equipped with a 1m×1m square aluminum tube magnetic field coil, it can achieve a maximum pulse magnetic field strength of 2000A/m. Adopt 7" TFT color touch screen, the operation interface is simple and convenient. Ethernet communication interface for remote microcomputer control).



HCWG front view



HMFG 100/1000 Field Coils

Features

- 7-inch touch color screen, simple and elegant UI, easy to operate Pulse
- waveform: 1.2/50 μ s_8/20 μ s
- Magnetic field coil: 1m×1m and 1m×2.6m
- Can edit a single test program and a combination of multiple programs
- Magnetic field strength: 100A/m ~ 2000A/m
- Coil holder included, polarity and height adjustable

Applications

- IEC/EN 610004-9, GB/T 17626 9

HCWG pulsed magnetic field test system





Technical Parameters


Output Voltage	HCWG 50 (0.2kV - 5.0kV)±10% HCWG 70 (0.2kV - 7.0kV)±10%	Output Current	HCWG 50 (100A - 2.5kA)±10% HCWG 70 (100A - 3.5kA)±10%
Voltage rise time	1.2μs±30%	Current rise time	8μs±20%
Voltage duration	50μs±20%	Current duration	20μs±20%
Polarity	Positive/negative/alternate	Counter	1 - 9999
Source impedance	2Ω	Peak voltage monitor	Automatic display and BNC output(1000:1)
Phase Sync	0-359°/1° each step Sync:external/internal:Async Mode	Peak current monitor	Automatic display and BNC output(1kA/V)
Standard option	CDN coupling:IEC or ANSI	Automatic programming	Synchro-phase/voltage/coupling path

Pulse magnetic field test level

Level	Pulse magnetic field strength (A/m)
1	NA
2	NA
3	100
4	300
5	1000
×	special

Software running interface





Order No.	Name	Model	Describe
41030100	lightning surge generator	HCWG 50	7" touch screen Surge: $\pm 5\text{kV}$, 1.2/50 μs
41030200	lightning surge generator	HCWG 70	7" touch screen Surge: $\pm 7\text{kV}$, 1.2/50 μs
41050140	magnetic field antenna	HHS 100	Single turn of aluminum tube: 1m \times 1m

The leader of EMC Test and Measurement



Address : Fuhai • Bao'an • Shenzhen

Tel : +86 755-27210748

E-mail : office@htec-emc.com

Website : www.htec-emc.com

